

壁装式插座
货号 27006




- # 带螺钉接线端子
- # 外部固定
- # 从顶部穿入电缆

技术信息

伏特	32 A
极数	4 p
电压	400 V
钟点位置	6 h
赫兹	50–60 Hz
连接方式	螺钉连接
触点	标准
防护等级	IP 44
重量	355 克
认证标志	VDE, EAC, CQC

图纸



Drawing 1 MB 463 Dim. in mm	Amp. Poles	16			32		
		3	4	5	3	4	5
a		95	93	92.5	102	102	102
b		73.5	87.5	87.5	94	94	94
c		93	107.5	110	115.5	115.5	119.5
d		55.5	55.5	55.5	62	62	62
e		61	76	76	84	84	84
f1		5.3	5.3	5.3	5.1	5.1	5.1
f2		5.3	5.3	5.3	5.1	5.1	5.1
h		139	139	136.5	160	160	156.5
i		19.8	21.5	21.5	26.5	26.5	26.5
M		M20x	M25x	M25x	M25x	M32x	M32x
Terminal for cond. cross section (mm²) min.-max.		1.5 1.5 1.5	1.5 1.5 1.5	1.5 1.5 1.5	2.5 2.5 2.5	2.5 2.5 2.5	2.5 2.5 2.5
		—4	—4	—4	—6	—6	—6