


Panel mounted receptacle

Part number: 75042



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- MetalLine
- aluminium enclosure
- silver plated contacts, highly heat resistant contact carrier
- straight insertion direction
- sea water products are available on request
- if required, pilot cables can be introduced separately into enclosures, please add "PK" to the part number

Technical Details

Panel mounted receptacle	75042
Ampere	250A
Number of poles	4p
Clock position	7h
Nominal voltage AC	500V
Nominal frequency	50 - 60 Hz
Protection type IP	IP67
Contact carrier	silver plated contacts, highly heat resistant contact carrier
X-CONTACT	no
Connection	cage terminals
Contact screw drive	allen key
Pilot contact	2 pilot contacts
Pilot contact switch	no
Hole spacings	127 x 127 mm
Insertion direction	straight
Highly resistant to chemicals	no
Military version	no
Tightening torque connection terminal	16 Nm
Strip length jacket	200 mm
Strip length solid conductor	60 mm
Conductor cross-section min.	70 mm ²
Conductor cross-section max.	240 mm ²
Conductor cross-section pilot max.	4 mm ²
Weight (net)	9540 g

Panel mounted receptacle	75042
Packaging unit	1 pcs
Quantity per pallet	18 pcs
EAN / identification number	4015394151463

Permissible ambient conditions

	Min.	Max.
Permissible ambient temperature	-40 °C	100 °C

Material properties

Housing	aluminium grey [no RAL colour code]
Front part	aluminium grey [no RAL colour code]
Hinged lid	metal grey [no RAL colour code]

Material resistance

The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.

Material and environmental properties

RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓
Halogen-free	yes

Regulations and Standards

Norm	DIN EN IEC 60309
Declaration of Conformity	CE

Dimensional Drawing

Drawing
1 MB 388

Dim. in mm

