


Panel mounted inlet RAPIDO

Part number: 919



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- screw connection technology
- central fixing
- a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

Technical Details

Panel mounted inlet RAPIDO	919
Product serie	RAPIDO
Ampere	16A
Number of poles	3p
Clock position	4h
Nominal voltage AC	110V
Nominal frequency	50 - 60 Hz
Protection type IP	IP44
Contact carrier	standard
Connection	screw terminals
Tightening torque connection terminal	PZ2, slot
Phase inverter	without phase inverter
Pilot contact	without pilot contact
Insertion direction	straight
Type of mounting	central fixing
Military version	no
Protection cap	without protection cap
Tightening torque connection terminal for cable cross-section 1,0 - 1,5 mm ²	0.8 Nm
Tightening torque connection terminal for cable cross-section 2,5 - 4,0 mm ²	0.8 Nm
Recommended wire end treatment for supply cable connection terminal	ferrule square gasproof crimped
Strip length conductor	8 - 10 mm
Conductor cross-section min.	1.5 mm ²
Conductor cross-section max.	4 mm ²
Weight (net)	210 g

Panel mounted inlet RAPIDO	919
Packaging unit	10 pcs
Quantity per pallet	1520 pcs
EAN / identification number	4015394207634

Permissible ambient conditions		
	Min.	Max.
Permissible ambient temperature	-25 °C	40 °C
Average temperature over 24 hours		35 °C


Material properties	
Front part	PA6 yellow [similar RAL 1021]

Material resistance	
The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.	

Material and environmental properties	
RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓
Halogen-free	yes

Regulations and Standards	
Norm	DIN EN IEC 60309-2
Declaration of Conformity	CE
Test label	VDE (ÜG)

Dimensional Drawing



Drawing	Amp. Poles	16		
		3	4	5
2 MB 215				
Dim. in mm	a	69	69	69
	b	44	50	56
	c	45	43	42
	k max.	30	30	30
	h	70	70	70
	l	61	61	61
	l1	33.25	33.25	33.25
	†	wall thicknesses 2-9mm		
Terminal for cond. cross		1.5	1.5	
section (mm²) min.-max.		—4	—4	